



**CHESTNUT**  
P R O D U C T S

**SAFETY DATA SHEET**  
**Spirit Stain**

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name** Spirit Stain

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Air drying paint/lacquer product for interior use.

**Uses advised against** No specific uses advised against are identified.

**1.3. Details of the supplier of the safety data sheet**

**Supplier** Chestnut Products  
PO BOX 260,  
Stowmarket,  
IP14 9BX  
+44 (0) 1473 890118  
+44 (0) 1473 206522  
mailroom@chestnutproducts.co.uk

**1.4. Emergency telephone number**

**Emergency telephone** +44 (0)1473 425878 (09:00-17:00 Mon- Fri)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification**

**Physical hazards** Flam. Liq. 2 - H225

**Health hazards** Acute Tox. 4 - H302 Eye Irrit. 2 - H319 STOT SE 2 - H371

**Environmental hazards** Not Classified

**Classification (67/548/EEC or 1999/45/EC)** F; R11. Xn; R22, R68/20/21/22. Xi; R36

**2.2. Label elements**

**Pictogram**



**Signal word**

Danger

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H302 Harmful if swallowed.  
H319 Causes serious eye irritation.  
H371 May cause damage to organs .

## Spirit Stain

<b>Precautionary statements</b>	<p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with national regulations.</p>
<b>Contains</b>	Methanol
<b>Supplementary precautionary statements</b>	<p>P233 Keep container tightly closed.</p> <p>P240 Ground/bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P260 Do not breathe vapour/spray.</p> <p>P270 Do not eat, drink or smoke when using this product.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor.</p> <p>P330 Rinse mouth.</p> <p>P337+P313 If eye irritation persists: Get medical advice/attention.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p>

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>Ethanol</b>	<b>50 - 100%</b>
CAS number: 64-17-5	EC number: 200-578-6
Substance with National workplace exposure limits.	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 2 - H225	F; R11
<b>4-Hydroxy-4-methylpentan-2-one</b>	<b>25 - &lt;50%</b>
CAS number: 123-42-2	EC number: 204-626-7
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Eye Irrit. 2 - H319	Xi; R36

## Spirit Stain

<b>Methanol</b>	<b>5 - &lt;10%</b>
CAS number: 67-56-1	EC number: 200-659-6
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 2 - H225	F; R11. T; R23/24/25, R39/23/24/25
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
STOT SE 1 - H370	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical attention.
<b>Skin contact</b>	Wash skin thoroughly with soap and water.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse with water. Do not rub eye. Get medical attention if any discomfort continues.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Possible risk of irreversible effects.
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Pain or irritation. Intoxication. Narcotic effect. Muscle weakness. Nausea, vomiting.
<b>Ingestion</b>	May cause discomfort if swallowed. Stomach pain. May cause nausea, headache, dizziness and intoxication.
<b>Skin contact</b>	This product is rapidly absorbed through the skin and may cause symptoms similar to those of ingestion.
<b>Eye contact</b>	Irritating to eyes. Visual disturbances, including blurred vision.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

## Spirit Stain

**Suitable extinguishing media** The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. This product is toxic.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Alcohols.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate area. No smoking, sparks, flames or other sources of ignition near spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Promptly remove any clothing that becomes contaminated.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. For waste disposal, see Section 13. Wash thoroughly after dealing with a spillage.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

## Spirit Stain

### 7.1. Precautions for safe handling

<b>Usage precautions</b>	Keep out of the reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from food, drink and animal feeding stuffs. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Do not handle broken packages without protective equipment. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Do not reuse empty containers.
<b>Advice on general occupational hygiene</b>	Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

<b>Storage precautions</b>	Store locked up. Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep containers upright. Protect containers from damage.
<b>Storage class</b>	Flammable liquid storage.

### 7.3. Specific end use(s)

<b>Specific end use(s)</b>	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Ethanol

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m<sup>3</sup>

##### 4-Hydroxy-4-methylpentan-2-one

Long-term exposure limit (8-hour TWA): WEL 50 ppm 241 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 75 ppm 362 mg/m<sup>3</sup>

##### Methanol

Long-term exposure limit (8-hour TWA): WEL 200 ppm 266 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 250 ppm 333 mg/m<sup>3</sup>

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

#### Ethanol (CAS: 64-17-5)

<b>DNEL</b>	Consumer - Oral; Long term systemic effects: 87 mg/kg/day Consumer - Dermal; Long term systemic effects: 206 mg/kg/day Industry - Dermal; Long term systemic effects: 343 mg/kg/day Consumer - Inhalation; Short term local effects: 950 mg/m <sup>3</sup> Industry - Inhalation; Short term local effects: 1900 mg/m <sup>3</sup> Consumer - Inhalation; Long term systemic effects: 114 mg/m <sup>3</sup> Industry - Inhalation; Long term systemic effects: 950 mg/m <sup>3</sup>
<b>PNEC</b>	- Fresh water; 0.96 mg/l - Sediment (Freshwater); 3.6 mg/kg - Marine water; 0.79 mg/l - Soil; 0.63 mg/kg

#### 4-Hydroxy-4-methylpentan-2-one (CAS: 123-42-2)

## Spirit Stain

### DNEL

Workers - Inhalation; Short term local effects: 240 mg/m<sup>3</sup>  
 Workers - Inhalation; Long term local effects: 66.4 mg/m<sup>3</sup>  
 Workers - Inhalation; Long term systemic effects: 66.4 mg/m<sup>3</sup>  
 Workers - Dermal; Long term systemic effects: 9.4 mg/kg/day  
 Consumer - Inhalation; Short term local effects: 120 mg/m<sup>3</sup>  
 Consumer - Inhalation; Long term local effects: 11.8 mg/m<sup>3</sup>  
 Consumer - Inhalation; Long term systemic effects: 11.8 mg/m<sup>3</sup>  
 Consumer - Dermal; Long term systemic effects: 3.4 mg/kg/day  
 Consumer - Oral; Long term systemic effects: 3.4 mg/kg/day

### PNEC

- Fresh water; 2 mg/l  
 - Marine water; 0.2 mg/l  
 - Intermittent release; 1 mg/l  
 - STP; 82 mg/l  
 - Sediment (Freshwater); 9.06 mg/kg  
 - Sediment (Marinewater); 0.91 mg/kg  
 - Soil; 0.63 mg/kg

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

### Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Butyl rubber. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

### Other skin and body protection

Wear appropriate clothing to prevent skin contamination.

### Hygiene measures

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

### Respiratory protection

Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.

### Environmental exposure controls

Keep container tightly sealed when not in use. Avoid release to the environment.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Various colours.
Odour	Characteristic.
Odour threshold	Not available.
pH	Not available.

## Spirit Stain

<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	78°C
<b>Flash point</b>	12°C
<b>Evaporation rate</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Vapour pressure</b>	<110 kPa @ 25°C
<b>Vapour density</b>	Not available.
<b>Relative density</b>	>1
<b>Solubility(ies)</b>	Soluble in water.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not applicable.
<b>Explosive properties</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising.

### 9.2. Other information

**Volatile organic compound** This product contains a maximum VOC content of 810 g/l.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** See the other subsections of this section for further details.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** The following materials may react strongly with the product: Oxidising agents.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.

### 10.5. Incompatible materials

**Materials to avoid** Oxidising materials. Acids - oxidising.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

## Spirit Stain

### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Acute Tox. 4 - H302 Harmful if swallowed.

**ATE oral (mg/kg)** 1,250.0

### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE dermal (mg/kg)** 3,750.0

### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE inhalation (vapours mg/l)** 37.5

### Skin corrosion/irritation

**Animal data** Based on available data the classification criteria are not met.

### Serious eye damage/irritation

**Serious eye damage/irritation** Causes serious eye irritation.

### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### IARC carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 2 - H371 May cause damage to organs .

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

### General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

### Inhalation

A single exposure may cause the following adverse effects: Pain or irritation. Intoxication. Narcotic effect. Muscle weakness. Nausea, vomiting.

### Ingestion

May cause discomfort if swallowed. Stomach pain. Nausea, vomiting.



## Spirit Stain

<b>Skin contact</b>	This product is rapidly absorbed through the skin and may cause symptoms similar to those of ingestion.
<b>Eye contact</b>	Irritating to eyes.
<b>Route of entry</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target organs</b>	No specific target organs known.

### SECTION 12: Ecological Information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

#### 12.1. Toxicity

**Toxicity** Based on available data the classification criteria are not met.

#### 12.2. Persistence and degradability

**Persistence and degradability** The product is expected to be biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

#### 12.4. Mobility in soil

**Mobility** The product is water-soluble and may spread in water systems. Volatile liquid. The product contains organic solvents which will evaporate easily from all surfaces.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** None known.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** The generation of waste should be minimised or avoided wherever possible. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

**Disposal methods** Containers should be thoroughly emptied before disposal because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

**General** For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

#### 14.1. UN number

**UN No. (ADR/RID)** 1263

**UN No. (IMDG)** 1263

## Spirit Stain

UN No. (ICAO) 1263

UN No. (ADN) 1263

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

### 14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

### Transport labels



### 14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ADN packing group II

ICAO packing group II

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-E, S-E

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## Spirit Stain

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	Health and Safety at Work etc. Act 1974 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### Inventories

##### EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

### SECTION 16: Other information

<b>Classification procedures according to Regulation (EC) 1272/2008</b>	Acute Tox. 4 - H302: STOT SE 2 - H371: Eye Irrit. 2 - H319: : Calculation method. Flam. Liq. 2 - H225: : Expert judgement.
<b>Training advice</b>	Read and follow manufacturer's recommendations.
<b>Revision comments</b>	Classification according to EC 1272/2008 (CLP).
<b>Revision date</b>	22/05/2015
<b>Revision</b>	2
<b>Supersedes date</b>	12/05/2014
<b>SDS number</b>	2863
<b>Risk phrases in full</b>	R11 Highly flammable. R22 Harmful if swallowed. R23/24/25 Toxic by inhalation, in contact with skin and if swallowed. R36 Irritating to eyes. R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. R68/20/21/22 Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

## Spirit Stain

<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H301 Toxic if swallowed. H302 Harmful if swallowed. H311 Toxic in contact with skin. H319 Causes serious eye irritation. H331 Toxic if inhaled. H370 Causes damage to organs . H371 May cause damage to organs .
----------------------------------	--

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.