Abrasive Mop Assembly
How to Assemble and Basic Use
Version 1.0

Each Abrasive Mop package comes with 24 abrasive strips. This will make 12 abrasive strip sets (2 abrasive strips set back to back equal a set).

Place one abrasive strip set on to the mandrel (2 abrasive strips back to back)

Place the next abrasive strip set on to the mandrel at a 90° angle to the first set.

Place the next abrasive strip set on to the mandrel at a 45° to the second set.

Place the next abrasive strip set on to the mandrel at a 90° angle to the last set.

Place a black washer on top of the previous abrasive strip set and push down on it firmly.
Repeat this entire process until you have used up all of the strips.

Once all the abrasive strips are on the mandrel, place the steel washer on to the last set of abrasive strips and firmly push it down. Secure the mop using the supplied nut. The nut is has a reverse thread to keep the mop secure while in use. Secure the nut while pinching the mop firmly (you may want to use gloves as protection while doing this) using a wrench. rasive strips and place them back to back to make up "one set" of abrasives and place on the mandrel.

Before using the abrasive mop, it is an absolute must that the mop is broken in. To do this, mount the mop to your drill press or hand held drill, power it on and run it up against a scrap piece of wood. Do this iuntil the tips of the mop are softened and resemble the image below.

You're now ready to start using the abrasive mop.