

Odie's General Application:

SHAKE or STIR WELL BEFORE USE. Apply small amounts of Odie's to the surface of the wood with a rag, brush, 0000 steel wool or an applicator pad (for best results use a scotch brite style pad whose grit is rated at or above the last grit level used on the wood/epoxy)-. Apply finish in the direction of the wood grain. Work the finish into the wood as you apply. Wait 30 minutes and check the wood surface. If the surface feels dry, apply more Odie's and repeat until the wood fiber is saturated and will not absorb any more finish. Allow finish to set for no less than 40 minutes and no longer than 20 hours. The longer the finish sets the harder it will be to buff off. Buff off with a cotton cloth to a lustrous sheen. You should buff it completely dry then allow to set for 3 days before use. You should wait for the full cure time of 2 to 3 weeks before letting any liquid on the wood surface. After the full cure time it will be water proof, if you applied the Odie's correctly, and if you have buffed all of the product off. For dense, hard surfaces such as epoxy or veneer the application process will be the same, however, you will only need to use a minuscule amount of oil. The great thing about Odie's Oil and its companion products is there is no wrong way to finish with them. Just remember - **Use all Odie's finishes like a wax**. Apply the product, wait for it to set up and vigorously buff off to a beautiful luster! The only hard rule is that all of the Odie's finishes should be completely buffed from the surface.

Odie's Oil

- Use for exotic woods.
- Use to achieve any luster level desired.
- Use for exterior or interior applications.
- Use as a wood stabilizer and sealer.

Odie's Dark Oil

- Use to darken wood and bring forward blacks and contrast with age.
- Use for an ambering effect.
- Use to achieve an antique effect on oak and pine.
- Great on mahogany, cherry and darker woods, including all exotics.
- Intended for interior use.

Odie's Wood Butter


- Like Odie's Oil, Odie's Wood Butter is a great wood finish and stabilizer. It also will achieve a higher luster than Odie's Oil and Odie's Dark Oil and with less color change.
- Use over Odie's Oil or Odie's Dark Oil to increase sheen and stability.
- Use to turn wet wood and to stabilize wet or problematic wood projects.
- Works great on exotic woods.
- Use in conjunction with other Odie's products to get a wet high luster look.
- Use for exterior or interior applications.

Odie's Wax

- Use alone or as a high luster wax over any finish.
- Use over light colored wood when minimal color change is desired.
- Great for white maple, it will increase the sheen with virtually no color change.
- Use in conjunction with other Odie's products to get a wet high luster look.

*Video and
More Information
Online*

Scan this QR code with your mobile device
or type the URL below into a web browser.



https://www.ptreeusa.com/turn_brand_odies_oil.html

Questions?

Thank you for choosing Peachtree Woodworking Supply. We highly value our customers and we always do our best and strive to make sure that you are satisfied with your buying experience with us.

We have put a great deal of effort into packing and shipping high quality tools and accessories and hope that the products you purchase from us either meet or exceeds your expectations.

If for some reason you have any issues or are in need of parts from your order, please don't hesitate to contact us. We will do our absolute best to make it right.

Call us toll free: **1-888-512-9069**

Email: peachtreesevice@aol.com Website: www.ptreeusa.com