Mr. Cornwall's Creative Colours

Welcome to Mr. Cornwall's Creative Colours-pure powdered pigments. Created for the master and amateur alike. These are 100% pure, finely ground pigments, refined from the natural metals of the earth. Our pigments are of the finest quality, are fully oxidized and completely stable, meaning they will not fade over time. They offer excellent UV protection, sunscreen for the wood!

We chose a pure powdered pigment system to provide the best quality materials to our customers to ultimately use as tools in the Odie's system of all-natural finishing to create decorative stains, custom-made patinas and colour-matched protective finishes for all woodworking projects including flooring, interior/exterior furniture and artwork, doors, decks, gates, siding and more.

Staying true to the Odie's system, there is no one way of doing things! You are never stuck in a box when using any Odie's product. This system is designed to give you all the tools you need and put you in full control! Make as little or as much stain as needed to complete a project, minimizing waste. Add more or less pigment to control saturation of colour and even mix in other pigments to customize the colour, value and tone. Utilize the different bases for the stain (oil, oil/solvent, wood butter and even the wax!) to really tune in your colours and stand out from the crowd!

Getting started: Making a basic stain.

There are three basic ways of blending a stain

(1) Oil based stain with Odie's Oil, Super Duper Oil or Solvent Free Super Penetrating Oil.

How to apply

Choose the desired pigment and mix/stir it in very well with the selected oil. Apply with a nonwoven pad (rated equal to or higher than your last sanding) in small circular motions, working the stain into the surface. Once buffed in, let set for 10 minutes to no longer than one hour. Buff off completely using a quality terry cotton towel until dry to touch. Allow to cure for 3-5 days then topcoat with your Odie's finish of choice.

(2) Solvent based version:

How to apply

Mix 1 part Odie's Oil or Super Duper Oil with up to 2 parts Odie's Safer Solvent. Add desired pigment and mix/shake well. The pigments may settle so be sure to keep the solution mixed

well throughout the staining process. Apply with a non-woven pad (rated equal to or higher than your last sanding) in small circular motions, working the stain into the surface. Once buffed in, let set for 10 minutes to no longer than one hour. Buff off completely using a quality terry cotton towel until dry to touch. Let cure for 3-5 days then top coat with your Odie's finish of choice.

(3) Making a patinating wax:

Fold and mash the desired pigment into the Wood Butter or Odie's Wax on a paint pallet. Work a thin coat into surface using a non-woven pad (rated equal to or higher than your last sanding) let set up for approximately 1 hour and buff off all excess.

Hints and tips

-Start with a small amount of pigment, you can always add more pigment to deepen the colour.

-Blend different pigments together to create custom colours.

-Water pop for a deeper impregnation of colour.

-For accurate repeatable stains, measure pigment and oil by weight.

<u>Important</u>

Always run some samples and test product on a spare surface or inconspicuous area for colour before applying to the finished project!

Final notes

-Wood is a natural material. Each species and each piece may finish differently.

-Surface preparation is of utmost importance for a beautiful finish, be thorough and diligent! -Colour is subjective, and beauty is in the eye of the beholder.